

# REMORQUES UTILITAIRES / UTILITY TRAILERS



Modèle représenté GV5699S2P



Modèles représentés GV5699TGS - GV56123TGS - GV6699TGS - GV66123TGS



Modèles représentés GV5699TG - GV56123TG - GV6699TG - GV66123TG

## REMORQUES / TRAILERS

|   | GV5699S2P               | GV5699TGS               | GV5699TG                | GV56123TGS              | GV56123TG               | GV6699TGS               | GV6699TG                |
|---|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Longueur hors tout/Overall length         | 143"/363,22 cm          | 143"/363,22 cm          | 143"/363,22 cm          | 171"/434,34 cm          | 171"/434,34 cm          | 143"/363,22 cm          | 143"/363,22 cm          |
| Largeur hors tout/Overall width           | 74"/187,96 cm           | 74"/187,96 cm           | 74"/187,96 cm           | 74"/187,96 cm           | 74"/187,96 cm           | 84"/213,36 cm           | 84"/213,36 cm           |
| Hauteur du sol au plancher/Overall height | 19"/48,26 cm            | 19"/48,26 cm            | 20"/50,80 cm            | 19"/48,26 cm            | 20"/50,8 cm             | 19"/48,26 cm            | 20"/50,8 cm             |
| Main d'attachement/Coupler                | 2"/5,08 cm              | 2"/5,08 cm              | 2"/5,08 cm              | 2"/5,08 cm              | 2"/5,08 cm              | 2"/5,08 cm              | 2"/5,08 cm              |
| <b>Plate-Forme / Trailer-bed</b>          |                         |                         |                         |                         |                         |                         |                         |
| Masse nette/Weight (lb/kg)                | 500 lb/227,27 kg        | 525 lb/238,64 kg        | 675 lb/306,82 kg        | 575 lb/261,36 kg        | 725 lb/329,55 kg        | 575 lb/261,36 kg        | 725 lb/329,55 kg        |
| G.V.W.R./P.N.B.V. (lb/kg)                 | 2156 lb/980 kg          | 2156 lb/980 kg          | 2816 lb/1280 kg         | 2156 lb/980 kg          | 2816 lb/1280 kg         | 2156 lb/980 kg          | 2816 lb/1280 kg         |
| Longueur/Inside length                    | 99"/251,46 cm           | 99"/251,46 cm           | 99"/251,46 cm           | 123"/312,42 cm          | 123"/312,42 cm          | 99"/251,46 cm           | 99"/251,46 cm           |
| Largeur/Inside width                      | 56"/142,24 cm           | 56"/142,24 cm           | 56"/142,24 cm           | 56"/142,24 cm           | 56"/142,24 cm           | 66"/167,64 cm           | 66"/167,64 cm           |
| Hauteur des côtés/Panel height            | 16"/40,64 cm            | 16"/40,64 cm            | 16"/40,64 cm            | 16"/40,64 cm            | 16"/40,64 cm            | 16"/40,64 cm            | 16"/40,64 cm            |
| Structure d'acier/Steel structure         | Acier-Galv.             | Acier-Galv.             | Acier-Galv.             | Acier-Galv.             | Acier-Galv.             | Acier-Galv.             | Acier-Galv.             |
| <b>Jantes et pneus/Tires and Wheels</b>   |                         |                         |                         |                         |                         |                         |                         |
| Essieux/Axles (Simple/Double)             | 1x (3500 lb/1590,91 kg) | 1x (3500 lb/1590,91 kg) | 2x (3500 lb/1590,91 kg) | 1x (3500 lb/1590,91 kg) | 2x (3500 lb/1590,91 kg) | 1x (3500 lb/1590,91 kg) | 2x (3500 lb/1590,91 kg) |
| Traction extérieure/Outside traction      | 74"/187,96 cm           | 74"/187,96 cm           | 74"/187,96 cm           | 74"/187,96 cm           | 74"/187,96 cm           | 84"/213,36 cm           | 84"/213,36 cm           |
| Jantes d'acier/Steel rims                 | 13X4.5 galv.            | 13X4.5 galv.            | 13X4.5 galv.            | 13X4.5 galv.            | 13X4.5 galv.            | 13X4.5 galv.            | 13X4.5 galv.            |
| Pneus sans tube/Tubeless tires            | 2x ST175-80-D13         | 2x ST175-80-D13         | 4x ST175-80-D13         | 2x ST175-80-D13         | 4x ST175-80-D13         | 2x ST175-80-D13         | 4x ST175-80-D13         |