

TRAILERS RST SERIES

General Cargo Trailer with Spring Axles



Shown with optional ladder racks, front ladder, two-tone package, RV Flush lock, bright aluminum front corners and gutter rail with black vinyl insert.

Shown with optional ramp door and roof vent.

Toll Free: (877) 283-7260

51790 County Road 39 • Middlebury, IN 46540

www.RCTrailers.com



RST SERIES

General Cargo Trailer with Spring Axles

| Standards a | and S | pecific | ation | s |
|-----------------------------------|---------|---------|---------|-----------|
| Item | 5' Wide | 6' Wide | 7' Wide | 8.5' Wide |
| 3/16" Lauan Walls | • | • | • | • |
| Undercoated Frame | • | • | • | • |
| 3/4" Advantech Flooring | • | • | • | • |
| (2) Dome Lights w\Switch | • | • | • | • |
| DOT Exterior Lighting | • | • | • | • |
| Sealed Beam Tail Lights | • | • | • | • |
| Rear Door Type | Single | Double | Double | Double |
| 24" ATP Stoneguard | • | • | • | • |
| Coupler | 2" | 2" | 2-5/16" | 2-5/16" |
| 2,000 lb Top Wind Jack w\Sand Pad | • | • | • | • |
| .030 Aluminum Exterior | • | • | • | • |
| Aluminum Fenders | • | • | • | • |
| Sidewall Post Spacing* | 24" | 24" | 24" | 16" |
| Roof & Floor O.C. Spacing* | 24" | 24" | 24" | 24" |
| White Mod Wheels | • | • | • | • |
| 15" Bias Ply Tires | • | • | • | • |

^{*} When the GVWR is 9,900 lbs. or greater, the floor spacing is 16" on-center.

| Dimensions | | | | | | | | |
|-------------------------------|------------|---------|---------|-----------|--|--|--|--|
| Item | 5' Wide | 6' Wide | 7' Wide | 8.5' Wide | | | | |
| Side Door | 24" (opt)* | 32"* | 36"* | 36"* | | | | |
| Apx. Hitch Height | 17" | 17" | 18" | 18" | | | | |
| Apx. Interior Height | 60" | 72" | 72" | 78" | | | | |
| Apx. Interior Width | 56" | 67" | 80" | 96" | | | | |
| Apx. Exterior Height | 80" | 94" | 97" | 105" | | | | |
| Apx. Rear Door Opening Height | 54" | 66" | 66" | 72" | | | | |
| Apx. Rear Door Opening Width | 50.5" | 62.5" | 74.5" | 90.5" | | | | |

^{*} On shorter tandem axle models, a small door may be necessary and on 8'/8.5' wide trailers that are 18' and longer, a 48" door is standard. Please consult with your dealer if you have any questions. Thank You!

| | S | ize | a n d | Axle | e Co | mbir | nations |
|---|-------------------|-------------------|-------------------|-------------------|-------------------|--------------------|--|
| | Single Axle | | Tandem Axle | | xle | Legend | |
| Size | 2,900 lb. GVWR | 3,500 lb. GVWR | 5,200 lb. GVWR | 7,000 lb. GVWR | 9,900 lb. GVWR | 12,000 lb. GVWR | |
| 5' x 8' 5' x10' 5' x 12' | | | | | | | Not Available 2" x 3" tube 2" x 4" tube |
| 6' x 8' 6' x 10' 6' x 12' 6' x 14' 6' x 16' | | | | | | | 2" x 6" tube, 11 ga. 2" x 6" tube, 7 ga. Please see your dealer for available sizes for 8' and 8.5' wide models. |
| 7' x 10' 7' x 12' 7' x 14' 7' x 16' | | | | | | | Every trailer is backed by our 3-year Limited Warran Please see |
| 7' x 18' 7' x 20' | | | | | | | your dealer for detail |



Tailor your trailer to your exact needs with your choice of options. Some of our popular options include:

- Roof Vent (powered and non-powered)
- Rear Stabilizer Jacks
- Ramp Door (standard and heavy duty)
- 16" On-Center Wall Posts
- Sidewall Vents
- 3/4" Treated Plywood Floor
- 3/8" Plywood Walls
- RV Flush Lock



Your Professional RC Trailer Dealer is:

6/6/2013

Toll Free: (877) 283-7260 51790 County Road 39 • Middlebury, IN 46540 www.RCTrailers.com